

STEROTOP

Technical Data Sheet

DESCRIPTION:

STEROTOP has cleaning, water softening, disinfecting and deodorizing properties. This product is non-corrosive to stainless steel, natural and synthetic rubber, plastic, glass, etc. STEROTOP is a high alkaline chlorinated powder.

APPLICATIONS

STEROTOP can be used to clean equipment in the milk and food industries

SPECIFICATION:

Appearance:	Free flowing powder with a faint odour of chlorine
Colour:	White
P ^H (1% sol.)	12 – 13
Available chlorine	5.5-6.5%
Bulk density	800– 900 gr. / liter

DIRECTION FOR USE IN THE MILK INDUSTRY:

Always pre-dissolve powder in cold water, never add powder to hot water.

Circulate a hot solution (70°-80°C) around the plant at a concentration of 100gr per 40 liters of water. Circulate for a minimum of 10 minutes. Add cold water for cooling down the plant to 50°C, and then eject detergent to waste. Rinse with tap water until all detergent residues have been removed.

SAFETY and STORAGE INSTRUCTIONS

It is important to read label instructions before use! STEROTOP CONTAINS SODIUM HYDROXIDE. Sodium Hydroxide could cause severe burns. Avoid contact with acids as it liberates toxic chlorine gas. Do not use on aluminum. Keep out of reach of children. In case of contact with skin, wash with plenty of cold water.

In case of contact with eyes, rinse immediately with plenty of water and seek medical help. Prevent dust inhalation. Wear plastic gloves. Wear goggles.

Store in cool dry place. Avoid direct sunlight. Keep away from animal, and animal feedstocks. When not in use always keep container closed. Wipe over all spillages.